
### CBRSDSH2-100

# SURFACE MOUNT SILICON HIGH DENSITY 2.0 AMP SCHOTTKY BRIDGE RECTIFIER





www.centralsemi.com

## **DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CBRSDSH2-100 is a full wave bridge rectifier mounted in a durable epoxy surface mount case, utilizing glass passivated chips.

MARKING: FULL PART NUMBER

### **FEATURES:**

- High 2.0A Current Rating
- Low V<sub>F</sub> Schottky Diodes (700mV MAX @ I<sub>F</sub>=2.0A)

| MAXIMUM RATINGS: (T <sub>A</sub> =25°C unless otherwise noted) | SYMBOL              |             | UNITS |
|--|---------------------|-------------|-------|
| Peak Repetitive Reverse Voltage                                | $V_{RRM}$           | 100         | V     |
| DC Blocking Voltage  | $V_{R}$             | 100         | V     |
| RMS Reverse Voltage  | V <sub>R(RMS)</sub> | 70          | V     |
| Average Forward Current (T <sub>A</sub> =75°C)                 | IO                  | 2.0         | Α     |
| Peak Forward Surge Current (8.3ms)                             | <sup>I</sup> FSM    | 110         | Α     |
| Operating Junction Temperature                                 | $T_J$               | -50 to +125 | °C    |
| Storage Temperature  | T <sub>sta</sub>    | -50 to +150 | °C    |

### **ELECTRICAL CHARACTERISTICS PER DIODE**: (T<sub>A</sub>=25°C unless otherwise noted)


| SYMBOL  | TEST CONDITIONS      | TYP | MAX | UNITS |
|---------|----------------------|-----|-----|-------|
| $I_{R}$ | V <sub>R</sub> =100V | 1.0 | 50  | μΑ    |
| ٧F      | I <sub>F</sub> =2.0A | 650 | 700 | mV    |
| Cı      | Vp=4 0V f=1 0MHz     | 280 | 500 | рF    |

## CBRSDSH2-100

# SURFACE MOUNT SILICON HIGH DENSITY 2.0 AMP SCHOTTKY BRIDGE RECTIFIER



### **SMDIP CASE - MECHANICAL OUTLINE**



| DIMENSIONS |        |       |        |       |
|------------|--------|-------|--------|-------|
|            | INCHES |       | MILLIM | ETERS |
| SYMBOL     | MIN    | MAX   | MIN    | MAX   |
| Α          | 0.004  | 0.008 | 0.10   | 0.20  |
| В          | 0.040  | 0.060 | 1.02   | 1.52  |
| С          | 0.009  |       | 0.23   |       |
| D          | 0.290  | 0.310 | 7.37   | 7.87  |
| Е          | 0.086  | 0.098 | 2.18   | 2.49  |
| F          | 0.038  | 0.042 | 0.97   | 1.07  |
| G          | 0.316  | 0.335 | 8.03   | 8.51  |
| Н          | 0.195  | 0.205 | 4.95   | 5.21  |
| J          | 0.245  | 0.255 | 6.22   | 6.48  |
| K          | 0.360  | 0.410 | 9.14   | 10.41 |

SMDIP (REV: R1)

MARKING: FULL PART NUMBER


R3 (4-January 2013)


#### CBRSDSH2-100


# SURFACE MOUNT SILICON HIGH DENSITY 2.0 AMP SCHOTTKY BRIDGE RECTIFIER




### TYPICAL ELECTRICAL CHARACTERISTICS









#### **OUTSTANDING SUPPORT AND SUPERIOR SERVICES**



#### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

#### **DESIGNER SUPPORT/SERVICES**

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- · Package details
- Application notes
- · Application and design sample kits
- Custom product and package development

#### REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

#### **CONTACT US**

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: <a href="https://www.centralsemi.com/wwreps">www.centralsemi.com/wwreps</a>

**Worldwide Distributors:** 

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <a href="https://www.centralsemi.com/terms">www.centralsemi.com/terms</a>

www.centralsemi.com (001)



# Product End of Life Notification

| PDN ID:            | PDN01137   |
|--------------------|------------|
| Notification Date: | 11/22/19   |
| Last Buy Date:     | Stock Only |
| Last Shipment Date | Stock Only |

Please be advised that Central Semiconductor must immediately discontinue the product(s) listed in the attached PDN notice. We are unable to accept any further orders for these products **unless** we have available inventory on hand.

You may have purchased one or more of the products listed. Please do not hesitate to contact your local Central Semiconductor sales representative with any questions or needs you may have. Central regrets any inconvenience this may cause.

Sincerely,

Central Semiconductor Corp.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002



# Product End of Life Notification

| PDN ID:                   | PDN01137   |
|---------------------------|------------|
| <b>Notification Date:</b> | 11/22/19   |
| Last Buy Date:            | Stock Only |
| Last Shipment Date        | Stock Only |

Summary: Central's 2.0 amp Schottky bridge rectifiers in the SMDIP package are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

| Central Part Number | Replacement       |
|---------------------|-------------------|
| CBRSDSH2-100        | CBRHDSH2-100 TR13 |
| CBRSDSH2-100 TR13   | CBRHDSH2-100 TR13 |
| CBRSDSH2-40 BK      | CBRHDSH2-40 BK    |
| CBRSDSH2-40 TR13    | CBRHDSH2-40 TR13  |
| CBRSDSH2-60 BK      | CBRHDSH2-100 TR13 |
| CBRSDSH2-60 TR13    | CBRHDSH2-100 TR13 |

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002