


Central Semiconductor Corp.
Central Semiconductor Corp.
Central Semiconductor Corp.
 145 Adams Avenue
 Hauppauge, New York 11788



1N4454

SILICON SWITCHING DIODE

JEDEC DO-35 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1N4454 type is a high speed Silicon Switching Diode designed for computer and general purpose applications.

MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$)

	<u>SYMBOL</u>		<u>UNITS</u>
Peak Repetitive Reverse Voltage	V_{RRM}	75	V
Average Forward Current	I_O	150	mA
Forward Steady-State Current	I_F	200	mA
Peak Forward Surge Current (1.0 μs pulse)	I_{FSM}	4000	mA
Power Dissipation	P_D	500	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +200	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

<u>SYMBOL</u>	<u>TEST CONDITIONS</u>	<u>MIN</u>	<u>MAX</u>	<u>UNITS</u>
BV_R	$I_R = 5.0\mu\text{A}$	75		V
I_R	$V_R = 50\text{V}$		100	nA
I_R	$V_R = 50\text{V}, T_A = 150^\circ\text{C}$		100	μA
V_F	$I_F = 10\text{mA}$		1.0	V
C_T	$V_r = 0, f = 1.0\text{MHz}$		2.0	pF
t_{rr}	$V_R = 6.0\text{V}, I_F = 10\text{mA}, I_{rr} = 1.0\text{mA}, R_L = 100\Omega$		2.0	ns
t_{rr}	$I_F = I_R = 10\text{mA}, I_{rr} = 1.0\text{mA}$		4.0	ns

CentralTM
Semiconductor Corp.

145 Adams Avenue
 Hauppauge, NY 11788 USA
 Tel: (631) 435-1110 • Fax: (631) 435-1824
 www.centrasemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms