

CFTVS3V3B

**SURFACE MOUNT SILICON  
BI-DIRECTIONAL  
TRANSIENT VOLTAGE SUPPRESSOR**



[www.centrasemi.com](http://www.centrasemi.com)



**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CFTVS3V3B is a low leakage, fast response, bi-directional TVS in the space saving SOD-882 surface mount package. This device is designed to protect sensitive equipment connected to high speed data lines against ESD damage.

**MARKING CODE: 3**

**APPLICATIONS:**

- Data line protection
- User interface protection
- Charging/power port protection

**FEATURES:**

- Space saving SOD-882 package
- Low leakage current

**MAXIMUM RATINGS:** ( $T_A=25^\circ\text{C}$ )

Peak Power Dissipation (8x20 $\mu\text{s}$ )  
 Electrical Fast Transient (IEC 61000-4-4) (5x50ns)  
 ESD Voltage (IEC 61000-4-2, Air)  
 ESD Voltage (IEC 61000-4-2, Contact)  
 Operating Junction Temperature  
 Storage Temperature

**SYMBOL**

$P_{PK}$                       40  
 EFT                            40  
 $V_{ESD}$                         30  
 $V_{ESD}$                         30  
 $T_J$                             -55 to +125  
 $T_{stg}$                          -55 to +150

**UNITS**

W  
 A  
 kV  
 kV  
 $^\circ\text{C}$   
 $^\circ\text{C}$

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^\circ\text{C}$ )


Maximum Reverse Stand-off Voltage $V_{RWM}$	Minimum Breakdown Voltage $V_{BR} @ I_T$	Test Current $I_T$	Maximum Reverse Leakage Current $I_R @ V_{RWM}$	Maximum Clamping Voltage (8x20 $\mu\text{s}$ ) $V_C @ I_{PP}$		Typical TLP Clamping Voltage (Note 1) $V_{CL} @ I_{PP}$		Typical Dynamic Resistance (Note 1) $R_{DYN}$	Maximum Junction Capacitance @ 0V Bias $C_J$
				V	A	V	A		
3.3	3.5	2.0	0.5	6.5	1.0	6.0	4.0	0.25	10
				8.0	5.0	7.0	8.0		

Note 1: Transmission Line Pulse (TLP) conditions:  $Z_0=50\Omega$ ,  $t_p=100\text{ns}$


  
**CFTVS3V3B**  
**SURFACE MOUNT SILICON**  
**BI-DIRECTIONAL**  
**TRANSIENT VOLTAGE SUPPRESSOR**




**SOD-882 CASE - MECHANICAL OUTLINE**



TOP VIEW



SIDE VIEW



BOTTOM VIEW R2

SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.037	0.042	0.95	1.05
B	0.022	0.026	0.55	0.65
C	0.000	0.002	0.00	0.05
D	0.017	0.022	0.45	0.55
E	0.014		0.36	
F	0.017	0.022	0.45	0.55
G	0.008	0.013	0.22	0.32

SOD-882 (REV:R2)

**PIN CONFIGURATION**



**LEAD CODE:**

- 1) Anode 1
- 2) Anode 2

**MARKING CODE: 3**

R8 (28-July 2015)


CFTVS3V3B



SURFACE MOUNT SILICON  
BI-DIRECTIONAL  
TRANSIENT VOLTAGE SUPPRESSOR



### Definition of Electrical Characteristics







R8 (28-July 2015)

  
**CFTVS3V3B**  
**SURFACE MOUNT SILICON**  
**BI-DIRECTIONAL**  
**TRANSIENT VOLTAGE SUPPRESSOR**



**TYPICAL ELECTRICAL CHARACTERISTICS**






R8 (28-July 2015)

  
**CFTVS3V3B**  
**SURFACE MOUNT SILICON**  
**BI-DIRECTIONAL**  
**TRANSIENT VOLTAGE SUPPRESSOR**



**TYPICAL ELECTRICAL CHARACTERISTICS**



R8 (28-July 2015)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)



http://www.centrasemi.com

# Product End of Life Notification

<b>PDN ID:</b>	PDN01241
<b>Notification Date:</b>	8/03/22
<b>Last Buy Date:</b>	2/03/23
<b>Last Shipment Date</b>	8/03/23

Summary: The CFTVS3V3B TVS is discontinued and now classified as End Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Portfolio Management. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

**\* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.**

<b>Central Part Number</b>	<b>Suggested Replacement</b>
CFTVS3V3B BK	N/A
CFTVS3V3B TR	N/A

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit <https://my.centrasemi.com/submit-inquiry?type=ER> to submit an online inquiry.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.